



# V A L V E S

## In-Line Flow Control Valves



### FEATURES:

- Carbon steel body
- Designed to provide precision flow control & shut off in one flow direction & provide free flow in the opposite direction
- Color bands allow fast return to a previous setting
- Set screw locks valve to any setting

## Model In-Line Flow Control Valves

| MODEL No. | PORT SIZE | MAX PSI   | MAX FLOW | SHIPPING WEIGHT | LIST PRICE |
|-----------|-----------|-----------|----------|-----------------|------------|
| WFC-400   | 1/4" NPTF | 5,000 PSI | 5 GPM    | 0.5             | 33.00      |
| WFC-600   | 3/8" NPTF | 5,000 PSI | 8 GPM    | 0.9             | 35.50      |
| WFC-800   | 1/2" NPTF | 5,000 PSI | 15 GPM   | 1.5             | 44.00      |
| WFC-1200  | 3/4" NPTF | 3,000 PSI | 25 GPM   | 2.5             | 85.50      |
| WFC-1600  | 1" NPTF   | 3,000 PSI | 40 GPM   | 3.5             | 208.00     |

| MODEL NO. | MAX FLOW | A        | B    | C    | D    | E    | F    | G   | H    |
|-----------|----------|----------|------|------|------|------|------|-----|------|
| WFC-400   | 19       | 1/4 NPTF | 1.79 | 1.59 | 2.62 | 1.66 | .81  | .41 | .811 |
| WFC-600   | 30       | 3/8 NPTF | 2.18 | 1.94 | 2.75 | 1.75 | 1    | .5  | 1    |
| WFC-800   | 57       | 1/2 NPTF | 2.70 | 2.42 | 3.44 | 2.23 | 1.25 | .63 | 1.19 |
| WFC-1200  | 95       | 3/4 NPTF | 3.38 | 2.81 | 3.88 | 2.58 | 1.5  | .75 | 1.38 |
| WFC-1600  | 151      | 1 NPTF   | 4.87 | 4.21 | 5    | 3.22 | 1.75 | .88 | 1.88 |

